



SPECIFICATION SHEET

44-5745

SEAMLESS KNIT ENGINEERED YARN GLOVE WITH PREMIUM NITRILE COATED MICROFOAM GRIP ON PALM & FINGERS

- Innovative fibres - ATG® sources their base ingredients to develop their own unique high performance yarns and fibers that offer cut protection while maintaining high levels of comfort.
- 360° breathability - patented Nitrile MicroFoam coating offers 360° breathability, making it the most breathable glove on the market today.
- Form, fit and feel - mimics the "hand at rest", reducing hand fatigue and increasing comfort.
- Latest knitting technology - utilized to produce smooth and rounded fingertips, improving fingertip sensitivity.
- Consistent liner penetration - from the nitrile, leaving only the soft liner resting against the skin.
- All ingredients used in the manufacturing and construction of this product are compliant with the REACH legislation.
- This glove has been laundered prior to final packaging making it clean and safe for use.
- The Oeko-Tex® Association has evaluated and certified this product as skin safe from the second it comes into contact with the skin.
- The Skin Health Alliance has awarded professional dermatological accreditation following review of the scientific dossier behind this product.
- Silicone Free

APPLICATIONS

- DIY and Gardening
- Finishing and inspection
- Handling of small components
- Primary, secondary and final assembly
- Maintenance
- Logistics and warehousing
- Using tools and instruments

CARE INSTRUCTIONS

Recommend washing gloves in slightly warm water not exceeding 40°C. A mild non-ionic detergent should be used. A 5-10 minute cycle time should be employed. Tumble dry on low - maximum temperature 140°F (60°C)

TECHNICAL DATA

MATERIAL	Seamless knit engineered yarn, micro-foam nitrile coating					
COLOR	Black/Black					
CUFF STYLE	Knit Wrist					
SIZES	XS - XXL					
PACKAGING	12 per dozen, 6 dozen per case					
CASE	19.7" x 11.6" x 7.9" / 50cm x 29.5cm x 20cm					
CASE WEIGHT	XS	S	M	L	XL	XXL
	9.5lbs / 4.3kg	11lbs / 5kg	11.5lbs / 5.2kg	13lbs / 5.9kg	13.2lbs / 6kg	14.3lbs / 6.5kg
C00	Sri Lanka					

PERFORMANCE PROPERTIES

EN388: 4342E	ASTM F2992-15 ANSI Cut Level (Adopted by ANSI/ISEA 02/16) ASTM F1790-05 ANSI Cut Level					
ABRASION	0	1	2	3	4	5
CUT	0	1	2	3	4	5
TEAR	0	1	2	3	4	5
PUNCTURE	0	1	2	3	4	5
CUT (TDM-100)	A	B	C	D	E	F




BARCODES

ITEM	PAIR	DOZEN	CASE
44-5745/XS	616314406126	10616314406123	20616314406120
44-5745/S	616314406164	10616314406161	20616314406168
44-5745/M	616314406201	10616314406208	20616314406205
44-5745/L	616314406249	10616314406246	20616314406243
44-5745/XL	616314406287	10616314406284	20616314406281
44-5745/XXL	616314406324	10616314406321	20616314406328

DIMENSIONS (in/cm)

	XS	S	M	L	XL	XXL
A	8.3in / 21cm	8.7in / 22cm	9.1in / 23cm	9.4in / 24cm	9.8in / 25cm	10.2in / 26cm
B	3.5in / 9cm	3.8in / 9.6cm	3.9in / 10cm	4.1in / 10.5cm	4.2in / 10.7cm	4.3in / 11cm
H	Blue	Red	Orange	White	Yellow	Black



PROTECTIVE INDUSTRIAL PRODUCTS, INC. | BRINGING THE BEST OF THE WORLD TO YOU®

AMERICAS: (800) 262-5755 • (518) 861-0133 | EUROPE: +34-96182-41-48 | AMEA: (ASIA, MIDDLE EAST, AFRICA) 852-2475-9228 | www.pipglobal.com

This document and the information contained herein is the property of Protective Industrial Products, Inc. (PIP) and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of PIP products for a particular purpose or use within a particular environment. PIP DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED.