

RE-BAR-TIER®

RB655 Uses 16 ga. wire, #5 x #5 up to #8 x #9



One wrap / tie



STANDARD EQUIPMENT

2 Batteries
Battery charger
Case
Holster
(JH500)



OPTIONAL



Extension
bar
(JE500)

16 Ga. TIE WIRE

RB655 50 COILS/BOX

TW1525
Regular
steel wire

TW1525-EG
Electro
galv. wire

TW1525-PC
Polyester
coated wire



SPECIFICATIONS

Tool	RB655
Weight	7.2 lbs
Dimensions (H)x(W)x(L)	13 3/4" x 4" x 13 3/4"
Tying Speed	.8-1.1 seconds / tie
Wraps per tie	One wrap
Ties per coil	120 to 230 ties
Ties per charge	2 to 4 coils
Battery	JP509H (Ni-Mh)
Voltage	DC 9.6V (3.3 Ah)
Recharge Time	Approx. 30 minutes

CORDLESS REBAR CUTTER

PJRC160 25.2V Series

Cuts up to #5 Bar
176 cuts / charge
(290 cuts for #4)
Fast 3.3 sec/cut
Brushless motor
360° head rotation



LITHIUM-ION

WORLD'S FIRST BATTERY OPERATED REBAR TYING TOOL

In 1993, MAX developed the world's first battery-operated rebar tying tool for the Japanese market. Since then, MAX Rebar Tying Tools have been revolutionizing rebar tying work all around the world. The MAX Rebar Tying Tools are extremely fast and easy to use. Just pull the trigger and you can tie rebar in less than a second. By using them, you can also reduce the risk of health problems such as Carpal Tunnel Syndrome. Save time, save money, increase job productivity with MAX Rebar Tying Tools.

FEATURES

Quick tying ability, each tie takes less than one second
About 5 times faster than manual tying
One hand operation, speeds set-up time
Reduces risk of health problems
Lightweight & compact body
Learn to operate in just minutes



Both the National Institute for Occupational Safety and Health and Health Construction Safety Association of Ontario state the MAX Re-bar Tying Tool reduces the risk of Carpal Tunnel Syndrome and other work related musculoskeletal disorders.

APPLICATIONS FOR REBAR TYING TOOL



**COMMERCIAL BUILDING / FOUNDATIONS / ROAD CONSTRUCTION
BRIDGES / PRECAST PLANTS / RADIANT HEATING TUBES / BASEMENTS
ELECTRICAL CONDUITS / TILT-UP CONSTRUCTION / POOLS / SAND BAGS**



MAX

MAX USA CORP.

205 Express Street, Plainview, New York 11803
Phone: 800-223-4293 Fax: 516-741-3272
www.maxusacorp.com

09/2019 SMR# STF-006

MAX REBAR TYING TOOLS

TVINTIER™



WORLD'S FIRST BATTERY OPERATED REBAR TYING TOOL

RE-BAR-TIER®



TWINTIER™

RE-BAR-TIER®

WORLD'S FIRST BATTERY OPERATED REBAR TYING TOOL


RB441T

Uses 19 ga. wire,
ties up to #7 x #7

LITHIUM-ION



2 wires / tie
1 wrap



Up to
#7 x #7

19 Ga. TIE WIRE

30 COILS/BOX

TW1061T
Regular steel wire

TW1061T-EG
Electro galv. wire

TW1061T-PC
Polyester-coated wire



US Made Steel
Buy America Certified
Available in
regular steel wire

STANDARD EQUIPMENT

Battery pack JPL91440A
AC Battery charger JC925
Plastic carry case
Reversible belt hook (Left or Right)



Battery charger (JC925)

SPECIFICATIONS

Tool	RB441T
Weight	5.6 lbs.
Dimensions (H)x(W)x(L)	11 1/2" x 4 3/4" x 13"
Tying Speed	Approx. 1/2 Sec.
Ties per coil	Approx. 145 to 265
Ties per charge	Approx. 4000
Battery	JPL91440A
Voltage	DC 14.4V
Recharge Time	Approx. 40 minutes

RB398

Uses 21 ga. wire,
#3 x #3 up to #5 x #6

LITHIUM-ION



3 wraps / tie



Up to
#5 x #6

RB218

Uses 21 ga. wire,
ties up to #3 x #3

LITHIUM-ION



3 wraps / tie



Up to
#3 x #3

SPECIFICATIONS

Tool	RB398	RB218	RB518
Weight	5.3 lbs	5.3 lbs	5.3 lbs
Dimensions (H)x(W)x(L)	12" x 4 1/8" x 11 3/8"	12" x 4 1/8" x 10 3/8"	12" x 4 1/8" x 11 3/8"
Tying Speed	Less than 1 sec. / tie	Less than 1 sec. / tie	Less than 1 sec. / tie
Wraps per tie	3 wraps	3 wraps	3 wraps or 4 wraps
Ties per coil	Approx. 120	Approx. 170 to 210	Approx. 90 (3 wraps) Approx. 75 (4 wraps)
Ties per charge	Approx. 2,600 ties	Approx. 3,000 ties	Approx. 2,400 ties (3 wraps) Approx. 2,200 ties (4 wraps)
Battery	JPL91440A (Lithium-ion Battery)		
Voltage	DC 14.4V		
Recharge Time	Approx. 40 minutes		

RB518

Uses 21 ga. wire,
#5 x #5 up to #7 x #8

LITHIUM-ION



3 wraps / tie OR 4 wraps / tie



Up to
#7 x #8

21 Ga. TIE WIRE

RB398/
RB518/RB218

50 COILS/BOX
TW898
Regular steel wire

(TW898-EG is not recommended for use in the RB518)
TW898-EG
Electro galv. wire

TW898-PC
Polyester-coated wire



US Made Steel
Buy America Certified
Available in
regular steel wire

STANDARD EQUIPMENT

RB398/RB518/RB218

Battery pack JPL91440A
AC Battery charger JC925
Plastic carry case
Reversible belt hook (Left or Right)



Battery charger (JC925)

OPTIONAL EQUIPMENT

Extension
bar (JE400)

Tool cover (JT450)

